



12feet Height PVC Tarpaulin Inflatable Water Park Outdoor Jumping Tower Slide

Our Product Introduction

Basic Information

- Place of Origin: GuangZhou, China
- Brand Name: King Inflatable
- Certification: CE, UL, SGS, EN71, EN14960
- Model Number: IF-WP(67)
- Minimum Order Quantity: 5 PCS
- Price: Negotiable
- Packaging Details: PVC bags+carton
- Delivery Time: In 10 days
- Payment Terms: T/T, L/C, Western Union, Money Gram, Euro account, US dollar account
- Supply Ability: 500pcs/month



Product Specification

- Material: 0.9mm PVC Tarpaulin
- Workmanship: Heat Sealed
- Size: 12feet (3.7m) Height Or Customize
- Highlight: giant inflatable pool floats, blow up water toys



Product Description

12feet Height PVC Tarpaulin Inflatable Water Park Outdoor Jumping Tower Slide

Specifications:

Model number:	IF-WP (67)
workmanship:	Heat sealed
Type:	Inflatable Water Park Outdoor Jumping Tower Slide
Material:	0.6/0.9mm PVC tarpaulin, anti-ripped
Color:	customize
Pump voltage:	110 or 220V is available

Application:

1. Water proof and fire resistant, can be used in the rainy and sunny days.
2. People climbing up the top of the slide, and sliding down into water, or jumping into the water on the top of the tower.
3. Hooks at the bottom to tie a weight for anchoring
4. Any sizes, shapes/designs, colors according to customer requirements
5. 12feet Height PVC Tarpaulin Inflatable Water Park Outdoor Jumping Tower Slide can be widely used as summer water park, water game parks, sun cold paradise amusement water park, for outdoor use.

Advantages:

1. Strong and nice welds
2. Sealed type, do not need continuous air blow.
3. Various colors are available
4. We can print logos, banners or artworks on it
5. Durable, 4-6 years usage life span
6. Easy to assemble, to move and to pack,
7. Once broken, it's easy to repair and work again.
8. The best material is very important for water games. All inflatable water games of Topfun are made by high durability fire-retardant PVC Tarpaulin, which has 3 layers, two coated sides with a strong net inside. The flame retardant meets BS7837. Our material has improved by the SGS.

Order procedures:

1. Contact us by send a inquiry, discuss all the instructions and details of each item of the order on email, skype or whatsapp etc., reach an agreement include item size, material, color, shape, how to print the logos or artworks, delivery time, shipping methods, payment terms, warranty clauses etc.
2. We make the proforma Invoice/contract, put the drawing/design in it with all the negotiated instructions and details in it for customer confirmation.
3. Customer send us the first payment deposit to get the order started. We start to get the right materials and accessories, ready for the production.
4. Our designers will make a professional 3d picture with notes for customer check again, and meanwhile, make the computer designs for cutting, sew, hot air welding dept with measurements and explanations in Chinese for workers cutting piece by piece.
5. Sewing / welding dept get the pieces, with the computer designs created by the our designers, join the pieces together by sewing or welding.
6. Testing, each products will be tested for before shipment, and take the pictures for customer to check whether all the workout is meet all the requirements that negotiated. If all correct, customer pay the remaining balance, we ship out the order; if not, then point them out, we will make the modification, then send pictures to customer to check again.
7. Professional packing workers, they weigh and measure the item, and give us the datas, we record and save it for transportation reference. Packing list, Commercial Invoice and Bill of Lading, to send all the documents and certifications that required for customer to do the custom clearance.

Pictures:

12feet Height PVC Tarpaulin Inflatable Water Park Outdoor Jumping Tower Slide



King Inflatable Co.,Limited

+86 18620259154

kinkor@king-inflatable.com

inflatablewaterfun.com

Room 813, Building A, Jingshi Plaza, No.179 Yingbin Avenue, Huadu District, Guangzhou, China